



ARCHITECTURAL SYSTEM FOR COMMERCIAL AND RESIDENTIAL

1" ARCHITECTURAL SNAP-LOCK PANEL SYSTEM

Englert's Series 1101 system is designed for sloped roofs and other exterior surfaces of light commercial and residential projects. The 1101 profile, with a concealed integrated nail strip and fasteners, requires no mechanical seaming or separate seam cap. The narrow standing seam can be detailed to provide a smooth transition from roof to fascia or mansard. The cliplless design lends itself to fast and easy installations.

SYSTEM APPLICATIONS

- Light duty for residential and commercial use
- 3"/12" minimum slope
- Must be installed over a solid deck

SUBSTRATES

- 26 and 24 gauge steel
- .032" aluminum
- 16 oz. copper





FINISHES

Englert's Series 1101 system is available in a wide variety of coatings and colors. See the Englert color card for our full range of standard colors and paint system specifications.

Englert can match the color of virtually any material – including brick, wood and fabric – with short lead times as needed. Custom colors are available in quantities as low as 5,000 lbs. on steel or aluminum.

SYSTEM WARRANTIES


- Galvalume Plus® – 25-year steel warranty on acrylic coated Galvalume®
- PermaColor 2000 – 30-year steel or aluminum warranty on Kynar 500®/Hylar 5000® coating
- PermaMetallic 2000 – 20-year steel or aluminum warranty on Kynar 500®/Hylar 5000® coating
- Siliconized Modified Polyester – 15-year steel or aluminum coating warranty

RATINGS AND CERTIFICATIONS

- UL-90 rating pending
- ASTM-E-84 Class A fire rating on coating and substrate
- Metro-Dade County rating pending
- ASTM-E-1680-95 air infiltration rating pending
- ASTM-E-1646-95 water penetration rating pending



Series 1101 1" Integral Snap-Lock



Distributed by:

Kynar 500® is a registered trademark of Atochem. N.A.
Hylar 5000® is a registered trademark of Ausimont USA
Galvalume® and Galvalume Plus® are registered trademarks of BIEC International, Inc.

Copyright ©2011 Englert Inc. All rights reserved.

90350H